

# CROSS REFERENCE CHART

**APILUS**  
JUNIOR 3G

**APILUS**  
SENIOR 3G

**APILUS**  
PLATINUM  
*PURE*

**APILUS**  
xCell Pur

**APILUS**  
xCell Pro



FEATURES							
FREQUENCY	13.56 MHZ	•	•				
	27.12 MHZ			•	•	•	
THERMOLYSIS METHODS	THERMOLYSIS (13.56 MHZ HF CURRENT TO BE WORKED IN TENTHS OF A SECOND)	•					
	FLASH (13.56 MHZ HF CURRENT TO BE WORKED IN HUNDREDTHS OF A SECOND)	•	•				
	MICROFLASH (13.56 MHZ HF CURRENT TO BE WORKED IN THOUSANDTHS OF A SECOND)		•				
	PICOFLASH (ULTRARAPID 27.12 MHZ HF CURRENT TO BE WORKED IN THOUSANDTHS OF A SECOND)			•	•	•	
	MELOFLASH (ULTRARAPID 27.12 MHZ HF CURRENT TO BE WORKED IN HUNDREDTHS OF A SECOND)				•	•	
	FUNCTION PP/VD (TECHNIQUE THAT ALLOWS THE APPLICATION OF TWO REDUCED MICROFLASH OR PICOFLASH PULSES IN TWO DIFFERENT LOCATIONS IN THE FOLLICLE)			•	•	•	
	SYNCHRO (SYNCHRONIZED APPLICATION OF MULTIPLE ULTRARAPID 27.12 MHZ HF MICROPULSES)				OPTIONAL	OPTIONAL	•
BLEND METHODS	MULTIPLY (COMBINAISON OF SLOW THERMOLYSIS WITH A MICROFLASH OR PICOFLASH PULSE AT THE END)		•	•	•	•	
	EVOLUBLEND (SIMULTANEOUS APPLICATION OF A GRADUALLY INCREASING GLV CURRENT AND 27.12 MHZ HF CURRENT)				OPTIONAL	OPTIONAL	•
	PICOBLEND (CONTINUOUS GLV CURRENT WITH 27.12 MHZ HF PULSES)				•	•	•
	SYNCHROBLEND (CONTINUOUS GLV CURRENT WITH MULTIPLE ULTRARAPID 27.12 MHZ HF MICROPULSES)					OPTIONAL	•
	MULTIBLEND (CONTINUOUS COMBINATION OF GLV AND HF CURRENTS WITH A MICROFLASH OR PICOFLASH PULSE AT THE END)			•	•	•	•
	OMNIBLEND (CONTINUOUS COMBINATION OF GLV AND HF CURRENTS)	•	•	•	•	•	•
PULSING BLEND (CONTINUOUS GLV CURRENT WITH 13.56 MHZ HF PULSES)		•	•				
ELECTROLYSIS (CONTINUOUS GLV CURRENT)		•	•	•	•	•	
PRINTER						•	
TOLERANCE TEST		•	•	•	•	•	
IMM-PAC (INCLUDES MULTIPLY, MULTIBLEND, FUNCTION PP/VD AND PROGRAMS FOR USE WITH INSULATED PROBES)			•	•	•	•	
NB. OF PROGRAMS (CLASSIFIED BY BODY AREA, HAIR SIZE AND PROBE TYPE)		512	1080	1100 + 440 / SYNCHRO OPTION	19 800	29 700	
NB. OF PERSONALIZED PROGRAMS			60	50	60	100	
CATAPHORESIS MODE WITH PROGRAMS (SOOTING TREATMENT)		•	•	•	•	•	
ANAPHORESIS MODE		•	•	•	•	•	
MESO-IONIZATION		•	•	•	•	•	
SCREEN	REGULAR (80 CHARACTERS)	•	•				
	MONOCHROME WITH PICTOGRAMS (240 × 84 PIXELS)			•			
	COLOR TOUCH SCREEN (800 × 480 PIXELS)				•	•	
KEY TO CALCULATE U.L. (UNITS OF LYE IN BLEND)			•	•	•	•	
KEY TO CALCULATE E.L. (ENERGY LEVELS IN THERMOLYSIS)			•	•	•	•	
MODE OF OPERATION WITHOUT FOOTSWITCH		•	•	•	•	•	
MOISTURE TEST		•	•	•	•	•	
MANAGEMENT SYSTEM WITH CLIENT FILES						•	
SMART CARD SYSTEM						•	
COMPUTER LINK				•	• (USB PORT)	• (USB PORT)	
NB. OF PROBEHOLDER OUTLETS		1	2	2	2	2	
ACCESSORY TEST			•	•	•	•	
PROTECTION CIRCUIT AND CURRENT STABILITY MONITOR		•	•	•	•	•	
INTERNATIONAL POWER SUPPLY				•	•	•	